Composite Push-In Fittings

FOR USE WITH SAE J844 TUBING

PRODUCT FEATURES

- Easy to Assemble
- Designed to resist mechanical pull-out
- Can be repeatedly assembled and disassembled as needed
- Several parts available with or without a swivel pipe thread
- Swivel is for installation purposes only

TEMPERATURE RANGE

-40°F to 140°F (-40°C to 60°C)

WORKING PRESSURE

Up to 145 PSI

ASSEMBLY INSTRUCTIONS

- 1. Cut tubing squarely, maximum 15° angle allowable.
- 2. Check that the port of the mating part is clean.
- 3. Insert tubing into fitting until it bottoms. (Push at least twice to verify that tubing is inserted past collet & O-ring)
- 4. Pull on tubing to verify that it is fully inserted.
- To disassemble, simply press release collar, hold it against fitting body and simultaneously pull tubing out of the fitting.

PUSH-TO-CONNECT FITTING REMOVAL TOOL

This tool makes removing push-to-connect fittings quick and easy! P/N: TG-DUL03413





STRAIGHT MALE CONNECTOR



TS P/N	TUBE	PIPE
S768PMT-2-1*	1/8"	1/16"
S768PMT-2-2*	1/8"	1/8"
S768PMT-2-4*	1/8"	1/4"
S768PMT-532-1	5/32"	1/16"
S768PMT-532-2	5/32"	1/8"
S768PMT-532-4	5/32"	1/4"
S768PMT-4-2	1/4"	1/8"
S768PMT-4-4	1/4"	1/4"
S768PMT-4-6	1/4"	3/8"
S768PMT-6-2	3/8"	1/8"
S768PMT-6-4	3/8"	1/4"
S768PMT-6-6	3/8"	3/8"
S768PMT-6-8	3/8"	1/2"
S768PMT-8-4	1/2"	1/4"
S768PMT-8-6	1/2"	3/8"
S768PMT-8-8	1/2"	1/2"
S768PMT-10-6	5/8"	3/8"
S768PMT-10-8	5/8"	1/2"
S768PMT-12-6	3/4"	3/8"
S768PMT-12-8	3/4"	1/2"
S768PMT-12-12	3/4"	3/4"

* Non-DOT

FEMALE CONNECTOR



TS P/N	TUBE	PIPE
S766PMT-532-2	5/32"	1/8"
S766PMT-4-2	1/4"	1/8"
S766PMT-4-4	1/4"	1/4"
S766PMT-4-6	1/4"	3/8"
S766PMT-6-2	3/8"	1/8"
S766PMT-6-4	3/8"	1/4"
S766PMT-6-6	3/8"	3/8"
S766PMT-6-8	3/8"	1/2"
S766PMT-8-2	1/2"	1/8"
S766PMT-8-4	1/2"	1/4"
S766PMT-8-6	1/2"	3/8"
S766PMT-8-8	1/2"	1/2"

BULKHEAD FEMALE CONNECTOR



TS P/N	TUBE	PIPE
S786PMTBH-4-2	1/4	1/8
S786PMTBH-4-4	1/4	1/4
S786PMTBH-6-4	3/8	1/4
S786PMTBH-6-6	3/8	3/8
S786PMTBH-8-6	1/2	3/8
S786PMTBH-8-8	1/2	1/2

STRAIGHT UNION



TS P/N	TUBES
S762PMT-2*	1/8"
S762PMT-532	5/32"
S762PMT-532-4	5/32" & 1/4"
S762PMT-3*	3/16"
S762PMT-4	1/4"
S762PMT-6	3/8"
S762PMT-6-8	3/8" & 1/2"
S762PMT-8	1/2"
S762PMT-10	5/8"
S762PMT-12-12	3/4"

* Non-DOT

BULKHEAD UNION



TS P/N	TUBE
S762PMTBH-2*	1/8"
S762PMTBH-5/32-5/32	5/32"
S762PMTBH-4	1/4"
S762PMTBH-6	3/8"
S762PMTBH-8	1/2"
S762PMTBH-10	5/8"

* Non-DOT

MALE ELBOW



TS P/N	TUBE	PIPE	
S769PMT-2-2*	1/8"	1/8"	
S769PMT-2-4	1/8"	1/4"	
S769PMT-532-2	5/32"	1/8"	
S769PMT-532-4	5/32"	1/4"	
S769PMT-4-2	1/4"	1/8"	
S769PMT-4-4	1/4"	1/4"	
S769PMT-4-6	1/4"	3/8"	
S769PMT-6-2	3/8"	1/8"	
S769PMT-6-4	3/8"	1/4"	
S769PMT-6-6	3/8"	3/8"	
S769PMT-6-8	3/8"	1/2"	
S769PMT-8-4	1/2"	1/4"	
S769PMT-8-6	1/2"	3/8"	
S769PMT-8-8	1/2"	1/2"	
S769PMT-10-6	5/8"	3/8"	
S769PMT-10-8	5/8"	1/2"	
S769PMT-10-12	5/8"	3/4"	
S769PMT-12-8	3/4"	1/2"	
S769PMT-12-12	3/4"	3/4"	

* Non-DOT

FEMALE ELBOW



TS P/N	TUBE	PIPE
S770PMT-5/32-2	5/32"	1/8"
S770PMT-4-2	1/4"	1/8"
S770PMT-4-4	1/4"	1/4"
S770PMT-4-6	1/4"	3/8"
S770PMT-6-2	3/8"	1/8"
S770PMT-6-4	3/8"	1/4"
S770PMT-6-6	3/8"	3/8"
S770PMT-6-8	3/8"	1/2"
S770PMT-8-4	1/2"	1/4"
S770PMT-8-6	1/2"	3/8"
S770PMT-8-8	1/2"	1/2"

MALE **BRANCH "Y"**

TS P/N

S798YPMT-4-2

S798YPMT-4-4

S798YPMT-6-4

UNION "Y"

TS P/N S764YPMT-4

S764YPMT-4-4-6

S764YPMT-6 S764YPMT-6-6-4



1/8"

1/4"

1/4"

1/4"

1/4"

3/8"

MALE	
BRANCH	TEE



TS P/N	TUBE	PIPE
S772PMT-2-2*	1/8"	1/8"
S772PMT-2-4*	1/8"	1/4"
S772PMT-532-1	5/32"	1/16"
S772PMT-532-2	5/32"	1/8"
S772PMT-532-4	5/32"	1/4"
S772PMT-4-2	1/4"	1/8"
S772PMT-4-4	1/4"	1/4"
S772PMT-4-6	1/4"	3/8"
S772PMT-6-2	3/8"	1/8"
S772PMT-6-4	3/8"	1/4"
S772PMT-6-6	3/8"	3/8"
S772PMT-6-8	3/8"	1/2"
S772PMT-8-4	1/2"	1/4"
S772PMT-8-6	1/2"	3/8"
S772PMT-8-8	1/2"	1/2"
S772PMT-10-6	5/8"	3/8"
S772PMT-10-8	5/8"	1/2"

* Non-DOT

UNION **ELBOW**

45° MALE

TS P/N

ELBOW - SWIVEL



TS P/N	TUBE
S765PMT-5/32	5/32"
S765PMT-4	1/4"
S765PMT-6	3/8"
S765PMT-8	1/2"

UNION TEE



1/4"

1/4", 1/4", 3/8" 3/8"

3/8", 3/8", 1/4"

TS P/N	TUBES
S764PMT-2*	1/8"
S764PMT-532	5/32"
S764PMT-3*	3/16"
S764PMT-4	1/4"
S764PMT-4-4-6	1/4", 1/4", 3/8"
S764PMT-6	3/8"
S764PMT-6-6-4	3/8", 3/8", 1/4"
S764PMT-8	1/2"
S764PMT-8-8-6	1/2", 1/2", 3/8"
S764PMT-10	5/8"
	t Nam DO

* Non-DOT

FEMALE BRANCH TEE



TS P/N	TUBES	THREAD
S777PMT-4-2	1/4"	1/8"
S777PMT-4	1/4"	1/4"
S777PMT-6-4	3/8"	1/4"
S777PMT-8-6	1/2"	3/8"
S777PMT-10-4	5/8"	1/4"

S754PMT-2-2*	1/8"	1/8"
S754PMT-532-2	5/32"	1/8"
S754PMT-4-2	1/4"	1/8"
S754PMT-4-4	1/4"	1/4"
S754PMT-4-6	1/4"	3/8"
S754PMT-6-2	3/8"	1/8"
S754PMT-6-4	3/8"	1/4"
S754PMT-6-6	3/8"	3/8"
S754PMT-6-8	3/8"	1/2"
S754PMT-8-4	1/2"	1/4"
S754PMT-8-6	1/2"	3/8"
S754PMT-8-8	1/2"	1/2"
S754PMT-10-6	5/8"	3/8"
S754PMT-10-8	5/8"	1/2"
S754PMT-12-6	3/4"	3/8"
S754PMT-12-8	3/4"	1/2"

TUBE

* Non-DOT

MALE RUN TEE



TS P/N	TUBE	PIPE
S771PMT-5/32-1	5/32"	1/16"
S771PMT-532-2	5/32"	1/8"
S771PMT-532-4	5/32"	1/4"
S771PMT-4-2	1/4"	1/8"
S771PMT-4-4	1/4"	1/4"
S771PMT-4-6-4	1/4" & 3/8"	1/4"
S771PMT-6-4	3/8"	1/4"
S771PMT-6-6	3/8"	3/8"
S771PMT-6-8	3/8"	1/2"
S771PMT-8-4	1/2"	1/4"
S771PMT-8-4-8	1/2" & 1/4"	1/2"
S771PMT-8-6	1/2"	3/8"
S771PMT-8-8	1/2"	1/2"